



APL 3500 Series

Automatic Print & Apply Systems, technologically designed to meet the highest requirements of labeling in real time on production lines.

APL3500 Series Automatic Real-Time Labeling Systems, have been developed to meet the most strict requirements in terms of reliability, robustness and compatibility with industrial standards, established by the GS1 International for packaging:

- ✓ Top
- ✓ Side
- ✓ Front
- ✓ Rear
- ✓ Corner
- ✓ Double side

Technologically designed to meet the new production line requirements, in terms of high speed and high production volume **APL 3500 Series** can print and apply labels with variable data, up to 90 cases/minute.

APL 3500 Series are easy to install and integrate and offering a wide connectivity range to any IT or automatization system, through UBS Label CS® and UBS Labman® Software, that allow to manage and transmit data to or from any ERP, MES, WMS or DBMS.

APL 3500 Series meet the GS1 global standards of codification and traceability with ANSI barcode printing and grade A and B in GTIN codes.



PRINT&APPLY SYSTEMS

- ✓ **Automatic Print & Apply in real Time Labeling Systems, for any group packaging (cases, packs, trays, bags, etc.).**
- ✓ **Top, side, front, rear, corner and double side.**
- ✓ **Speed up to 90 labels/min.**
- ✓ **Fully manufactured out of anodized aluminium.**
- ✓ **Technologically designed to meet the highest requirements and highest production volumes.**





APL 3500 Series

Technical Features

PRINT ENGINE	ZEBRA, DATAMAX, SATO...
PRINTING RESOLUTION	From 203 up to 600 dpi (depending on print engine and printing speed)
REEL OF LABELS	Máx. diameter: up to 400 mm
REEL OF RIBBON	Max. length: 600 m (depending on print engine specifications)
LABELING SPEED	Up to 90 labels/min (depending on print engine and packaging dimensions)
INTERFACE	Ethernet, USB, Wifi, RS232 (depending on print engine specifications)
INTERFACE I/O	3 I/O free, expandable
DISPLAY	3.5" Touch Screen
WEIGHT	APL: 40kg (88.20 lb) - Telescopic support: 75kg (165.3 lb)
DIMENSIONS	APL: 391 x 675 x 515 mm (15.4" x 26.5" x 20.3")
POWER SUPPLY	110/240 VAC. Frequency 50 to 60 Hz
ENVIRONMENT	From +5°C up to 40°C
HUMIDITY	Between 20% - 85% non-condensing



PRINT&APPLY SYSTEMS

- ✓ **Compact, solid, reliable and compatible with any OEM print engine on the market.**
- ✓ **Meets GS1 global standards of codification and traceability with ANSI barcode printing and grade A and B in GTIN codes.**



United Barcode Systems

Labeling, Coding & Marking



www.ubscore.com

The right choice

UBS HEADQUARTERS (+34) 902 127 721
UBS NORTH AMERICA (+1) 760 480 0777
UBS SPAIN (+34) 902 195 591
UBS MEXICO (+52) 55 5572 4892
UBS BRAZIL (+55) 11 2709 8640
UBS ITALY (+39) 0224 972 120

info@ubscore.com
info.usa@ubscore.com
info.espana@ubscore.com
info.mexico@ubscore.com
info.brasil@ubscore.com
info.italy@ubscore.com

